



2012 AKA MANUAL

ADDENDUM No. 7.1

Issued: 3rd February, 2012

This Addendum No. 7.1 replaces Addendum No. 7 which referred to rule numbers 27.02.4 and 27.02.5 instead of 27.04.4 and 27.04.5.

As per Postal Vote – PV2012-03, the NKC by majority vote have approved the removal of the following rules from the 2012 AKA Manual, effective immediately.

Rule 27.04.4

4. From 1st January, 2012, for State Championships ONLY, this class will be restricted to use aluminium alloy hubs and aluminium alloy rims with the following control dimensions;
FRONT RIMS: Internal width between flanges to be between 117mm and 127mm.
Offset is free. Bearing front rims only. No 'bolt on' front hubs are permitted.
REAR RIMS: Internal width between flanges to be between 120mm and 152mm. Offset is free.

Rule 27.04.5

5. From 1st January, 2013, at all times, this class will be restricted to use aluminium alloy hubs and rims that comply with rule 27.04.4.

Rule 28.04.4

4. From 1st January, 2012, for State Championships ONLY, this class will be restricted to use aluminium alloy hubs and aluminium alloy rims with the following control dimensions;
FRONT RIMS: Internal width between flanges to be between 117mm and 127mm.
Offset is free. Bearing front rims only. No 'bolt on' front hubs are permitted.
REAR RIMS: Internal width between flanges to be between 120mm and 152mm. Offset is free.

Rule 28.04.5

5. From 1st January, 2013, at all times, this class will be restricted to use aluminium alloy hubs and rims that comply with rule 28.04.4.

Pam Arnett
National Secretary
Australian Karting Association