

# HOMOLOGATION AND TECHNICAL SPECIFICATION UPDATE BULLETIN

HOMOLOGATION	ROTAX 125 MICRO MAX	HOMOLOGATION NO.	110H
BULLETIN NO.	Rotax 5 (Micro Max)	BULLETIN DATE	22 March 2016

The information and specifications contained in this Homologation and Technical Specification Update Bulletin are to be read in conjunction with and form part of the homologation detailed herein.

### EXPLANATORY NOTES SUPPLIED BY THE MANUFACTURER'S REPRESENTATIVE.

As BRP Rotax have altered the specification of the exhaust socket it has been decided to increase the maximum diameter of (A) to 18.20 mm - already implemented in the (international) technical regulations 2016. Also the minimum measurement of (C) must be at least 18.5 mm.

### Homologation Document Reference (The section to which the Bulletin applies)

**Document:** ROTAX 125 MICRO MAX HOMOLOGATION

**Heading:** D.1 INTERNAL PROFILE OF THE EXHAUST DUCT AND D.5 EXHAUST SYSTEM



### Details:

Just exhaust sockets with gasket ring are legal to be used.

Diameter (A) must apply for a length (B) of at least **12.0 mm**.

Maximum inner diameter (A) of exhaust sockets are:  
125 Mini MAX: **18.20 mm**

The measurement (C) must be at least **18.5 mm**

