

HOMOLOGATION AND TECHNICAL SPECIFICATION UPDATE BULLETIN

HOMOLOGATION	Vortex DVS - SV	HOMOLOGATION NO.	119H
	(Senior)		
BULLETIN NO.	119H-1 Updated	BULLETIN DATE:	20 Dec. 2017
		UPDATED ON:	3 April 2018

The information and specifications contained in this Homologation and Technical Specification Update Bulletin are to be read in conjunction with and form part of the homologation detailed herein.

APPROVED SPARK PLUGS

Homologation Document 119H, Page 23 states the following in relation to Spark Plugs.

"SPARK PLUG:

- Only spark plugs approved by Karting Australia for use in the Vortex DVS SV engine will be permitted.
- Spark plug must be standard and have the original washer fitted.
- Shank length 18.5mm maximum. No machining permitted."

This Bulletin confirms the ONLY SPARK PLUGS THAT ARE APPROVED AS OF THIS DATE FOR USE IN THE VORTEX DVS-SV SENIOR ENGINE.

ENGINE. NGK Spark Plug (Co. Ltd			
"Normal" Operating Tem	peratures and Conditions			
NGK B105EGV	NGK B11EGV			
Cold and Wet Conditions	•	·		
NGK B10EG	NGK B10EGV	NGI	NGK BR10EIX	
NGK B95EGV	NGK B9EG	NGK B9EGV	NGK B9EIX	
Denso Corporation	•			
"Normal" Operating Tem	peratures and Conditions			
Denso IW34				
Cold and Wet Conditions	•	<u>.</u>		
Denso W31	Denso W29	Den	Denso W27	
Denso IW31	Denso IW29	Den	Denso IW27	